

IN THE CLAIMS

Please amend the claims as follows:

1-13. (Canceled)

14. (Currently Amended) A flow control hub, comprising:

a scoreboard memory device to maintain flow control status for a plurality of flows, wherein each of the flows is identified by an associated index in the scoreboard memory;
a selector to select a next flow having a flow control status to process; and
a message generator to generate a flow control message for the selected flow based on the flow control status maintained in said scoreboard memory device for the selected flow, wherein said message generator transmits the generated flow control message to a queue associated with the selected flow, and wherein said message generator invalidates the flow control status maintained in said scoreboard memory device subsequent to transmitting the generated flow control message.

15-17. (Canceled)

18. (Previously Presented) The apparatus of claim 14, further comprising

an address decoder to receive a flow control message from a destination desiring to modify flow of data thereto, and to determine an associated flow and scoreboard memory index for the flow control message; and

an updater to update the flow control status for the associated flow in said scoreboard memory device based on the received flow control message.

19. (Currently Amended) A method, comprising:

maintaining a flow control status for a plurality of flows in a memory device, wherein each of the flows is identified by an associated index in the memory device;
selecting a next flow having a flow control status to process; and

generating a flow control message for the selected flow based on the flow control status maintained in the memory device for the selected flow;

transmitting the generated flow control message to a queue associated with the selected flow; and

invalidating the flow control status maintained in the memory device for the selected flow.

20-21. (Canceled)

22. (Previously Presented) The method of claim 19, further comprising receiving a flow control message from a destination desiring to modify flow of data thereto;

determining an associated flow and memory device index for the flow control message; and

updating the flow control status for the associated flow maintained in said memory device based on the received flow control message.

23-34. (Canceled)

35. (Previously Presented) A device comprising:

a plurality of ingress ports to receive data from external sources and to store the data in a plurality of ingress queues, wherein the ingress queues are associated with flows, wherein the flows are associated with at least some subset of source, destination, and priority;

a plurality of egress ports to receive data from at least a subset of the plurality of ingress queues and to store the data in a plurality of egress queues prior to transmission, wherein the egress ports issue flow control messages to control flow of data to the egress ports based at least in part on capacity of the egress queues; and

a flow control hub to receive the flow control messages from the egress ports, to record a flow control status for an associated flow in a scoreboard memory based on the received flow control message, to discard the received flow control message subsequent to recording the flow

control status, to select next flow having a valid flow control status to process, to generate a flow control message for the next flow, and to forward the generated flow control message to ingress ports associated with the next flow.

36. (Previously Presented) The device of claim 35, wherein said flow control hub includes a comparator to compare the received flow control message with the flow control status maintained in said scoreboard memory device and update the flow control status maintained in the scoreboard memory device based at least in part on the comparison.

37. (Canceled)

38. (Previously Presented) A flow control hub comprising:
a memory device to maintain a flow control status for a plurality of flows, wherein a flow defines at least a path from a particular ingress port to a particular egress port and wherein a flow control status for a particular flow defines whether data is eligible for transmission for the particular flow;

a queuing device to receive flow control messages from at least one egress port, to update the flow control status in the memory device for associated flows, and to discard the flow control messages, wherein the flow control message may modify the transmission eligibility of data to the egress port for one or more flows; and

a dequeuing device to select a next flow having a flow control status to be processed, to generate a flow control message based on the next flow control status, and to forward the generated flow control message to associated ingress ports.

39-42. (Canceled)

43. (Previously Presented) A method comprising
maintaining a flow control status for a plurality of flows in a memory device, wherein a flow defines at least a path from a particular ingress port to a particular egress port and wherein a

flow control status for a particular flow defines whether data is eligible for transmission for the particular flow;

receiving flow control messages from at least one egress port, wherein the flow control message may modify the transmission eligibility of data to the egress port for one or more flows;

updating the flow control status in the memory device for associated flows based on the received flow control messages;

discarding the flow control messages after the memory device is updated;

selecting a next flow having a flow control status to be processed;

generating a flow control message based on the next flow control status; and

forwarding the generated flow control message to associated ingress ports.

44. (Previously Presented) The method of claim 43, further comprising invalidating a particular flow subsequent to the particular flow having a flow control message generated and forwarded.